



Insulation Joint Adhesive Tape **JTA**

Refrigerant pipe insulation is imposed longitudinal variation by thermal shrinkage. The joint of insulation involves some risk of condensation accidents.



Specification



Material : Aluminum foil + Adhesive tape with fiberglass (Center part)
Temperature Range : -10°C~60°C (14° F~140° F)

Code	Description	Size(WxL)	Color	Price	Pcs/Pkg
07396	JTA-100-I	100mm x 10m (4in. x 11yd)	Ivory	Open	12

Reference Table for Required Length of Insulation Joint Tape JTA

*The figures in the table are for reference purpose. Lengths may differ from table due to insulation's outer diameter. When applying, adjust the length according to actual insulation. Unit : mm (in)

Compliant Pipe Size(in)	6.35(1/4)	9.52(3/8)	12.70(1/2)	15.88(5/8)	19.05(3/4)	22.22(7/8)	25.40(1)	28.58(1 1/8)	31.75(1 1/4)	34.92(1 3/8)	38.10(1 1/2)	41.28(1 5/8)	44.45(1 3/4)	50.80(2)	53.98(2 1/8)
Insulation Thickness 10mm* (in)	85(3)	95(4)	120(5)	130(5)	140(6)	150(6)	160(6)	170(7)	180(7)	190(8)	200(8)	210(8)	220(9)	270(11)	280(11)
Insulation Thickness 20mm (in)	160(6)	170(7)	180(7)	190(8)	205(8)	210(8)	220(9)	230(9)	240(9)	250(10)	265(10)	275(11)	280(11)	305(12)	315(12)

* Insulation thickness for pipe size 6.35mm (1/4in.) and 9.52mm (3/8in.) is 8mm (0.3in.), and the one for 50.80mm (2in.) and 53.98 (2 1/8in.) is 15mm (0.6in.).

[How to use]

1. Remove all the dirt and dust from the surface, and butt joint the insulations without any gap.
2. When taping, make sure joint part of the insulation comes to the center of the tape.
3. Wrap a tape around insulation to pile up on each other at least 10mm (0.4in.), and press it with hands to fit into the (uneven) emboss film.

Contact

INABA DENKI SANGYO CO.,LTD.

OVERSEAS SALES DEPARTMENT
INABA DENKO PRODUCTS DIVISION

4-11-14, ITACHIBORI, NISHI-KU, OSAKA, JAPAN 550-0012
Tel: +81-6-4391-1920 Fax: +81-6-4391-1935

<http://www.INABA-DENKO.com/>

